


DOWNLIGHT SHERIFF I 940 25W 55° GREY PREMIUM WHITE ON/OFF

Article number: N208-K0001-PW940-HA-###-ZC02_650-##-###





GULUUL

LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 3398 [lm]

 Luminous flux
 2718 [lm]

 System power
 25 [W]

 Luminaire Efficiency
 109 [lm/W]

 Beam angle
 109 [lm/W]

Controller

MacAdam

36°

ON/OFF

3 SDCM

LUMINAIRE

Weight 1 [kg]
Protection rating IP , IK , class IP 65, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 27W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska