

DOWNLIGHT

DOWNLIGHT SHERIFF I 927 14W 55° GREY | ON/OFF

Article number: N208-K0001-RF927-H8-###-ZC01_350-##-###



COB

80

2700 [K] |

1555 [lm]

1244 [lm]

89 [lm/W]

ON/OFF

3 SDCM

14 [W]

36°



Down	liah	t I I	FD
DOWIN	nyn		

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

- E -	111	/11	NI /	۸ II	PI	F

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE				
1 [kg]				
IP 65, IK 3,				
GREY				
Glass				
220-240V 50-60Hz				

may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

Generated: 02.06.2024