

DOWNLIGHT

DOWNLIGHT SHERIFF I 940 21W 55° GREY | ON/OFF

Article number: N208-K0001-RF940-H8-###-ZC02_550-##-###



СОВ

90

4000 [K] |

2658 [lm]

2126 [lm]


101 [lm/W]

ON/OFF

3 SDCM

21 [W]

36°



D	own	ligh	t LED
_	• • • • • •		

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LU	JM	IIN	AI	RE	Ξ.

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAINE				
1 [kg]				
IP 65, IK 3,				
GREY				
Glass				
220-240V 50-60Hz				

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 32 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024