

DOWNLIGHT

DOWNLIGHT SHERIFF I 930 25W 55° BLACK HI EFFICIENT ON/OFF

Article number: N208-K0002-BB930-H8-###-ZC02_650-##-###



COB

90

3000 [K] HI EFFICIENT

4084 [lm]

3267 [lm]

131 [lm/W]

ON/OFF

3 SDCM

25 [W]

36°



_				 _
Dov	m	ial	ht.	г
	nı	ıu	ш.	L

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LUMINAIRE

Light colour CRI

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

Weight	1 [kg]
Protection rating IP , IK , class	IP 65, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024