

DOWNLIGHT

DOWNLIGHT SHERIFF I 935 23W 55° BLACK HI EFFICIENT ON/OFF

Article number: N208-K0002-BB935-H8-###-ZC02_600-##-###



COB

90

3500 [K] HI EFFICIENT

3624 [lm]

2899 [lm]

126 [lm/W]

ON/OFF

3 SDCM

23 [W]

36°



Q146

Down	lig	ht	LED

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LUMINAIRE

Light colour CRI

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

Weight	1 [kg]
Protection rating IP , IK , class	IP 65, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024