


DOWNLIGHT SHERIFF I 930 11W 55° BLACK PREMIUM WHITE ON/OFF

Article number: N208-K0002-HE930-HA-###-ZC01_250-##-###





cutout Ø140mm

LED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 1497 [lm]

 Luminous flux
 1197 [lm]

 System power
 11 [W]

 Luminaire Efficiency
 109 [lm/W]

 Beam angle
 109 [lm/W]

Controller

MacAdam

36°

ON/OFF

3 SDCM

LUMINAIRE

 Weight
 1 [kg]

 Protection rating IP , IK , class
 IP 65, IK 3,

 Luminaire colour
 BLACK

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 02.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska