

## DOWNLIGHT SHERIFF I 930 14W 55° BLACK CRI97 ON/OFF

Article number: N208-K0002-HI930-H8-###-ZC01\_350-##-###



LED	COB
Light colour	3000 [K] CRI97
CRI	90
Led chip flux	1575 [lm]
Luminous flux	1260 [lm]
System power	14 [W]
Luminaire Efficiency	90 [lm/W]
Beam angle	36°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

### LUMINAIRE

Weight	1 [kg]
Protection rating IP , IK , class	IP 65, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 16.07.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska