

DOWNLIGHT

DOWNLIGHT SHERIFF I 827 13W 55° BLACK | ON/OFF

Article number: N208-K0002-RF827-H8-###-ZC01_350-##-###



COB

80

2700 [K] |

1886 [lm]

1508 [lm]

116 [lm/W]

ON/OFF

3 SDCM

13 [W]

36°



\sim	~	110

Downlig	ht	
Downiig	нι.	

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

111	IIN	Δ	RF

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1 [kg]			
Protection rating IP , IK , class	IP 65, IK 3,			
Luminaire colour	BLACK			
Cover	Glass			
Operating voltage	220-240V 50-60Hz			

may change with product improvements due to technical advances.

Note: All data are typical values. Tolerance of measurements +/-10% System features

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024