


DOWNLIGHT SHERIFF I 930 23W 55° BLACK | ON/OFF

Article number: N208-K0002-RF930-H8-###-ZC02_600-##-###







COB Light colour 3000 [K] | CRI Led chip flux 2767 [lm] Luminous flux 2213 [lm] System power 23 [W] Luminaire Efficiency 96 [lm/W] Beam angle 36° Controller ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 1 [kg]
Protection rating IP , IK , class IP 65, IK 3,
Luminaire colour BLACK
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska