

# DOWNLIGHT SHERIFF I 935 34W 55° WHITE HI EFFICIENT ON/OFF

Article number: N208-K0003-BB935-H8-###-ZC03\_900-##-###



LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	90
Led chip flux	5253 [lm]
Luminous flux	4202 [lm]
System power	34 [W]
Luminaire Efficiency	124 [lm/W]
Beam angle	ON/OFF
Controller	3 SDCM
MacAdam	

### Downlight LED

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

### LUMINAIRE

Weight	1 [kg]
Protection rating IP , IK , class	IP 65, IK 3,
Luminaire colour	Glass
Cover	220-240V 50-60Hz
Operating voltage	

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska