

DOWNLIGHT

DOWNLIGHT SHERIFF I 940 27W 55° WHITE HI EFFICIENT ON/OFF

Article number: N208-K0003-BB940-H8-###-ZC02_700-##-###



COB

90

4000 [K] HI EFFICIENT

4385 [lm]

3508 [lm]


130 [lm/W]

ON/OFF

3 SDCM

27 [W]

36°



GULUUL	014

Down	ligh	t LEI	D

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

		 		10	-
- L	U	IIN	1 🗛	ιк	

Light colour CRI

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

Weight	1 [kg]
Protection rating IP , IK , class	IP 65, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

K 3, Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024