

DOWNLIGHT

DOWNLIGHT SHERIFF I 827 31W 55° WHITE | ON/OFF

Article number: N208-K0003-RF827-H8-###-ZC03_800-##-###



COB

80

2700 [K] |

4311 [lm]

3448 [lm]

111 [lm/W]

ON/OFF

3 SDCM

31 [W]

36°



(cut out)	Ø140

Down	liaht	I ED
DOWN	ngin	

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LU	MI	NAI	RE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1 [kg]	
Protection rating IP , IK , class	IP 65, IK 3,	
Luminaire colour	WHITE	
Cover	Glass	
Operating voltage	220-240V 50-60Hz	

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024