

DOWNLIGHT

DOWNLIGHT SHERIFF I 835 23W 55° WHITE | ON/OFF

Article number: N208-K0003-RF835-H8-###-ZC02_600-##-###



COB

80

3500 [K] |

3340 [lm]

2672 [lm]


116 [lm/W]

ON/OFF

3 SDCM

23 [W]

36°



-			
Down	liahi	ТЕ	1

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LU	JM	IIN	AI	RE	Ξ.

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

AMINAINE				
Weight	1 [kg]			
Protection rating IP , IK , class	IP 65, IK 3,			
Luminaire colour	WHITE			
Cover	Glass			
Operating voltage	220-240V 50-60Hz			

ninaire colour	WHITE
/er	Glass
erating voltage	220-240V 50

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.