

## DOWNLIGHT

## DOWNLIGHT SHERIFF I 840 31W 55° WHITE | ON/OFF

Article number: N208-K0003-RF840-H8-###-ZC03\_800-##-###



COB

80

4000 [K] |

4542 [lm]

3633 [lm]

117 [lm/W]

ON/OFF

3 SDCM

31 [W]

36°



(cut out	Ø140

Down	lial	h+		
Down	nai		ᄂᄃ	L

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LU	MI	NAI	RE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1 [kg]		
Protection rating IP , IK , class	IP 65, IK 3,		
Luminaire colour	WHITE		
Cover	Glass		
Operating voltage	220-240V 50-60Hz		

## Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 14.08.2024