


## DOWNLIGHT QUNA A 930 14W 36° GREY HI EFFICIENT ON/OFF

Article number: N210-K0001-BB930-H8-Q36-ZC01\_350-S7-###



3 SDCM





COB 3000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 2256 [lm] Luminous flux 1804 [lm] System power 14 [W] Luminaire Efficiency 129 [lm/W] Beam angle 36° Controller ON/OFF

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

## LUMINAIRE

MacAdam

 Weight
 1,5 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 GREY

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska