

DOWNLIGHT

DOWNLIGHT QUNA A 930 36W 36° GREY HI EFFICIENT ON/OFF

Article number: N210-K0001-BB930-H8-Q36-ZC03_950-S7-###





LED	COB
Light colour	3000 [K] HI
CRI	EFFICIENT
Led chip flux	90
Luminous flux	5801 [lm]
	4640 [lm]
System power	36 [W]
Luminaire Efficiency	129 [lm/W]
Beam angle	n a
Controller	36°
MacAdam	ON/OFF
	3 SDCM
UMINAIRE	

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

LU

Weight	1,5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

