


DOWNLIGHT QUNA A 930 27W 60° GREY HI EFFICIENT ON/OFF

Article number: N210-K0001-BB930-H8-Q60-ZC02_700-S7-###







COB 3000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 4378 [lm] Luminous flux 3502 [lm] System power 27 [W] Luminaire Efficiency 130 [lm/W] Beam angle 60° Controller ON/OFF MacAdam 3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

LUMINAIRE

 Weight
 1,5 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 GREY

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska