


DOWNLIGHT QUNA A 930 36W 60° GREY HI EFFICIENT ON/OFF

Article number: N210-K0001-BB930-H8-Q60-ZC03_950-S7-###





LED CC)	E	3	
--------	---	---	---	--

Light colour 3000 [K] HI EFFICIENT

Led chip flux

5801 [lm] Luminous flux

4640 [lm] System power

Luminaire Efficiency 129 [lm/W]

Beam angle

60° Controller

ON/OFF MacAdam

3 SDCM

LUMINAIRE

CRI

Weight 1.5 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Glass

Operating voltage 220-240V 50-

60Hz

36 [W]

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

5

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

(€ EM 2K

Generated: 27.09.2024





