

DOWNLIGHT

DOWNLIGHT QUNA A 935 31W 36° GREY HI EFFICIENT ON/OFF

Article number: N210-K0001-BB935-H8-Q36-ZC03_800-S7-###





OMINAIRE	
UMINAIRE	
	3 SDCM
MacAdam	ON/OFF
Controller	36°
Beam angle	122 [lm/W]
Luminaire Efficiency	31 [W]
System power	3778 [lm]
Luminous flux	4723 [lm]
Led chip flux	90
CRI	EFFICIENT
Light colour	3500 [K] HI
LED	COB

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

L

Weight	1,5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

