


## DOWNLIGHT QUNA A 957 23W 24° GREY SPECIAL ON/OFF

Article number: N210-K0001-CC957-H8-Q24-ZC02\_600-S7-###







LED COB

Light colour 5700 [K] SPECIAL

CRI 90

 Led chip flux
 3023 [lm]

 Luminous flux
 2418 [lm]

 System power
 23 [W]

 Luminaire Efficiency
 105 [lm/W]

 Beam angle
 24°

Controller ON/OFF
MacAdam 3 SDCM

## LUMINAIRE

Weight 1,5 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour Glass

Operating voltage 220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska