

DOWNLIGHT

DOWNLIGHT QUNA A 957 25W 24° GREY SPECIAL ON/OFF

Article number: N210-K0001-CC957-H8-Q24-ZC02_650-S7-###





LED	СОВ
Light colour	5700 [K] SPECIAL
CRI	90
Led chip flux	3255 [lm]
Luminous flux	2604 [lm]
System power	25 [W]
Luminaire Efficiency	104 [lm/W]
Beam angle	24°
Controller	ON/OFF
MacAdam	3 SDCM
UMINAIRE	
Weight	1,5 [kg]

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 32 3

+48 32 388 80 00

www.cora.pl cora@cora.pl

IP 20, IK 3,

220-240V 50-60Hz

GREY

Glass



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024