

## DOWNLIGHT

# DOWNLIGHT QUNA A 935 11W 12° GREY PREMIUM WHITE ON/OFF

Article number: N210-K0001-HE935-HA-Q12-ZC01\_250-S7-###





Light colour3500 [K] PREMIUM WHITECRI90Led chip flux1545 [m]Luminous flux1236 [m]System power11 [W]Luminaire Efficiency112 [m/W]Beam angle12°ControllerON/OFFMacAdam3 SDCM	LED	СОВ
CRI90Led chip flux91Luminous flux1545 [lm]System power1236 [lm]Luminaire Efficiency111 [W]Beam angle112 [lm/W]Controller12°MacAdamON/OFF	Light colour	
Led chip flux1545 [lm]Luminous flux1236 [lm]System power11 [W]Luminaire Efficiency112 [lm/W]Beam angle12°Controller0N/OFFMacAdam1000000000000000000000000000000000000	CRI	
1236 [Im]System power11 [W]Luminaire Efficiency112 [Im/W]Beam angle12°Controller0N/OFFMacAdamON/OFF	•	
Luminaire Efficiency 11 [W]   Beam angle 112 [Im/W]   Controller 12°   MacAdam ON/OFF		1236 [lm]
112 [lm/W]   Beam angle   Controller   MacAdam		11 [W]
Controller ON/OFF MacAdam		112 [lm/W]
MacAdam	Controller	
3 SDCM	MacAdam	
		3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

## LUMINAIRE

Weight	1,5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024