

DOWNLIGHT

DOWNLIGHT QUNA A 940 25W 60° GREY | ON/OFF

Article number: N210-K0001-RF940-H8-Q60-ZC02_650-S7-###





	LED	СОВ
	Light colour	4000 [K]
	CRI	90
	Led chip flux	3141 [lm]
	Luminous flux	2512 [lm]
	System power	25 [W]
	Luminaire Efficiency	100 [lm/W]
	Beam angle	60°
	Controller	ON/OFF
	MacAdam	3 SDCM
UMINAIRE		
	Weight	1,5 [kg]

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

IP 20, IK 3,

220-240V 50-60Hz

GREY

Glass



Street: Ignatza Hakuby 18 41-914 Bytom, Polska