

DOWNLIGHT

DOWNLIGHT QUNA A 820 31W 60° GREY MEAT PINK ON/OFF

Article number: N210-K0001-VE820-H8-Q60-ZC03_800-S7-###





UMINAIRE	
MacAdam	3 SDCM
Controller	ON/OFF
Beam angle	60°
Luminaire Efficiency	64 [lm/W]
System power	31 [W]
Luminous flux	1996 [lm]
Led chip flux	2495 [lm]
CRI	80
Light colour	2000 [K] MEAT PINK
LED	СОВ

1,5 [kg]

GREY

Glass

IP 20, IK 3,

220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024