


DOWNLIGHT QUNA A 942 37W 60° BLACK MEAT WHITE ON/OFF

Article number: N210-K0002-CC942-H8-Q60-ZC03_950-S7-###







COB 4200 [K] MEAT WHITE Light colour

CRI

90 Led chip flux 3539 [lm] Luminous flux 2831 [lm] System power 37 [W] Luminaire Efficiency 77 [Im/W] Beam angle 60° Controller

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 1,5 [kg] Protection rating IP, IK, class IP 20, IK 3, BLACK Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska