


DOWNLIGHT QUNA A 957 14W 36° BLACK SPECIAL ON/OFF

Article number: N210-K0002-CC957-H8-Q36-ZC01_350-S7-###







LED COB

Light colour 5700 [K] SPECIAL

CRI 90

Led chip flux 1820 [lm]

Luminous flux 1456 [lm]

System power 14 [W]

Luminaire Efficiency 104 [lm/W]

Beam angle 36°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 1,5 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements $\pm 1.0\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska