


DOWNLIGHT QUNA A 930 11W 12° BLACK PREMIUM WHITE ON/OFF

Article number: N210-K0002-HE930-HA-Q12-ZC01_250-S7-###



LED	COB
Light colour	3000 [K] PREMIUM WHITE
CRI	90
Led chip flux	1497 [lm]
Luminous flux	1197 [lm]
System power	11 [W]
Luminaire Efficiency	109 [lm/W]
Beam angle	12°
Controller	ON/OFF
MacAdam	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

LUMINAIRE

Weight	1,5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 16.07.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska