

DOWNLIGHT QUNA A 930 21W 60° BLACK PREMIUM WHITE ON/OFF

Article number: N210-K0002-HE930-HA-Q60-ZC02_550-S7-###



LED	COB

Light colour 3000 [K]
PREMIUM
CRI WHITE

Led chip flux 90

Luminous flux 3143 [lm]

System power 2514 [lm]

Luminaire Efficiency 21 [W]

Beam angle 120 [lm/W]

Controller 60°

MacAdam ON/OFF

3 SDCM

LUMINAIRE

Weight 1.5 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-

Operating voitage 220-240 V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 27.09.2024







Street: Ignatza Hakuby 18 41-914 Bytom, Polska