


DOWNLIGHT QUNA A 935 11W 24° BLACK PREMIUM WHITE ON/OFF

Article number: N210-K0002-HE935-HA-Q24-ZC01_250-S7-###







LED COB

Light colour 3500 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 1545 [lm]

 Luminous flux
 1236 [lm]

 System power
 11 [W]

 Luminaire Efficiency
 112 [lm/W]

 Beam angle
 112 [lm/W]

Controller

MacAdam

24°

ON/OFF

3 SDCM

LUMINAIRE

 Weight
 1,5 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 BLACK

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 16.07.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska