


## DOWNLIGHT QUNA A 930 20W 12° BLACK PREMIUM COLOR ON/OFF

Article number: N210-K0002-PC930-HA-Q12-ZC01\_500-S7-###







LED COB

Light colour 3000 [K] PREMIUM COLOR

CRI

90

 Led chip flux
 2200 [lm]

 Luminous flux
 1760 [lm]

 System power
 20 [W]

 Luminaire Efficiency
 88 [lm/W]

 Beam angle
 12°

Controller

MacAdam

3 SDCM

## LUMINAIRE

 Weight
 1,5 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 BLACK

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska