


## DOWNLIGHT QUNA A 930 14W 36° BLACK PREMIUM COLOR ON/OFF

Article number: N210-K0002-PC930-HA-Q36-ZC01\_350-S7-###







COB

3000 [K] PREMIUM COLOR Light colour

CRI

90 Led chip flux 1583 [lm] Luminous flux 1266 [lm] System power 14 [W] Luminaire Efficiency 90 [lm/W] Beam angle 36° Controller

ON/OFF MacAdam 3 SDCM

## LUMINAIRE

Weight 1,5 [kg] Protection rating IP, IK, class IP 20, IK 3, BLACK Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska