

DOWNLIGHT

DOWNLIGHT QUNA A 927 25W 60° BLACK | ON/OFF

Article number: N210-K0002-RF927-H8-Q60-ZC02_650-S7-###





LED	COB
Light colour	2700 [K]
CRI	80
Led chip flux	2888 [lm]
Luminous flux	2310 [lm]
System power	25 [W]
Luminaire Efficiency	92 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM
LUMINAIRE	
LOMINAIRE	
Weight	1,5 [kg]

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

IP 20, IK 3,

220-240V 50-60Hz

BLACK

Glass



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024