


## DOWNLIGHT QUNA A 930 27W 60° BLACK | ON/OFF

Article number: N210-K0002-RF930-H8-Q60-ZC02\_700-S7-###







COB Light colour 3000 [K] | CRI Led chip flux 3227 [lm] Luminous flux 2581 [lm] System power 27 [W] Luminaire Efficiency 96 [lm/W] Beam angle 60° Controller ON/OFF MacAdam 3 SDCM

## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

## LUMINAIRE

Weight 1,5 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska