

DOWNLIGHT

DOWNLIGHT QUNA A 820 14W 60° BLACK MEAT PINK ON/OFF

Article number: N210-K0002-VE820-H8-Q60-ZC01_350-S7-###





Light colour	
Light colour	2000 [K] MEAT PINK
CRI	80
Led chip flux	1253 [lm]
Luminous flux	1002 [lm]
System power	14 [W]
Luminaire Efficiency	72 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM
UMINAIRE	

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

L

Weight	1,5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska