


DOWNLIGHT QUNA A 825 19W 12° BLACK BREAD ON/OFF

Article number: N210-K0002-VF825-H8-Q12-ZC01_500-S7-###



3 SDCM





COB 2500 [K] BREAD Light colour CRI 2340 [lm] Led chip flux Luminous flux 1872 [lm] System power 19 [W] Luminaire Efficiency 99 [lm/W] Beam angle 12° Controller ON/OFF

LUMINAIRE

MacAdam

 Weight
 1,5 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 BLACK

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska