

## DOWNLIGHT

## DOWNLIGHT QUNA A 942 19W 60° WHITE MEAT WHITE ON/OFF

Article number: N210-K0003-CC942-H8-Q60-ZC01\_500-S7-###





LED	СОВ
Light colour	4200 [K] MEAT WHITE
CRI	90
Led chip flux	
Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam	1976 [lm]
	1580 [lm]
	19 [W]
	83 [lm/W]
	60°
	ON/OFF
	3 SDCM
UMINAIRE	
Weight	1,5 [kg]

## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

Cover

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

IP 20, IK 3,

220-240V 50-60Hz

WHITE

Glass

 $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 02.06.2024