


DOWNLIGHT QUNA A 930 27W 12° WHITE CRI97 ON/OFF

Article number: N210-K0003-HI930-H8-Q12-ZC02_700-S7-###







 LED
 COB

 Light colour
 3000 [K] CRI97

CRI 90

 Led chip flux
 2990 [lm]

 Luminous flux
 2392 [lm]

 System power
 27 [W]

Luminaire Efficiency 89 [lm/W]
Beam angle 12°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 1,5 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska