

DOWNLIGHT QUNA A 940 35W 24° WHITE PREMIUM WHITE ON/OFF

Article number: N210-K0003-PW940-HA-Q24-ZC03_900-S7-###



LED	COB
Light colour	4000 [K] PREMIUM
CRI	WHITE

Led chip flux 90

Luminous flux 454

Luminous flux 4545 [lm]
System power 3636 [lm]
Luminaire Efficiency 35 [W]

Beam angle 104 [lm/W]

Controller 24°

MacAdam ON/OFF

3 SDCM

60Hz

LUMINAIRE

Weight	1.5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.









Street: Ignatza Hakuby 18 41-914 Bytom, Polska