

## DOWNLIGHT

# DOWNLIGHT QUNA A 940 20W 60° WHITE PREMIUM WHITE ON/OFF

Article number: N210-K0003-PW940-HA-Q60-ZC01\_500-S7-###





LED	СОВ
Light colour	4000 [K] PREMIUM WHITE
CRI	
Led chip flux	90
Luminous flux	2663 [lm]
	2130 [lm]
System power	20 [W]
Luminaire Efficiency	107 [
Beam angle	107 [lm/W]
Controller	60°
Controller	ON/OFF
MacAdam	0.0001
	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

## LUMINAIRE

Weight	1,5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

