

DOWNLIGHT QUNA A 830 14W 12° WHITE | ON/OFF

Article number: N210-K0003-RF830-H8-Q12-ZC01_350-S7-###











LED COB

Light colour 3000 [K]

CRI 80

Led chip flux 1905 [lm]

Luminous flux 1524 [lm]

System power 14 [W]

Luminaire Efficiency 109 [lm/W]

Beam angle 12°

Controller ON/OFF

MacAdam 3 SDCM

LUMINAIRE

Weight 1.5 [kg]

Protection rating IP, IK, class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

(€ EH EK

Generated: 27.09.2024





