


## DOWNLIGHT QUNA A 835 23W 24° WHITE | ON/OFF

Article number: N210-K0003-RF835-H8-Q24-ZC02\_600-S7-###







COB Light colour 3500 [K] | CRI 3340 [lm] Led chip flux Luminous flux 2672 [lm] System power 23 [W] Luminaire Efficiency 116 [lm/W] Beam angle 24° Controller ON/OFF MacAdam 3 SDCM

## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

## LUMINAIRE

Weight 1,5 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska