


#### DOWNLIGHT

# DOWNLIGHT QUNA A 927 25W 60° WHITE | ON/OFF

Article number: N210-K0003-RF927-H8-Q60-ZC02\_650-S7-###





LED	СОВ
Light colour	2700 [K]
CRI	80
Led chip flux	2888 [lm]
Luminous flux	2310 [lm]
System power	25 [W]
Luminaire Efficiency	92 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

## LUMINAIRE

Weight	1.5 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50- 60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 27.09.2024

+48 32 388 80 00



Street: Ignatza Hakuby 18 41-914 Bytom, Polska