


## DOWNLIGHT QUNA A 825 27W 60° WHITE BREAD ON/OFF

Article number: N210-K0003-VF825-H8-Q60-ZC02\_700-S7-###



60°





COB 2500 [K] BREAD Light colour CRI 3169 [lm] Led chip flux Luminous flux 2535 [lm] System power 27 [W] Luminaire Efficiency 94 [lm/W]

Beam angle Controller ON/OFF MacAdam 3 SDCM

## LUMINAIRE

Weight 1,5 [kg] Protection rating IP , IK , class IP 20, IK 3, WHITE Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 12°, 24°, 36° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska