


DOWNLIGHT QUNA A MINI 930 31W 24° GREY HI EFFICIENT ON/OFF

Article number: N211-K0001-BB930-H8-R24-ZC03_800-S8-###



3 SDCM





COB 3000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 4956 [lm] Luminous flux 3964 [lm] System power 31 [W] Luminaire Efficiency 128 [lm/W] Beam angle 24° Controller ON/OFF

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

MacAdam

Weight 1,2 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements $\pm -10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska