


DOWNLIGHT QUNA A MINI 957 23W 36° GREY SPECIAL ON/OFF

Article number: N211-K0001-CC957-H8-R36-ZC02_600-S8-###







LED COB

Light colour 5700 [K] SPECIAL

CRI 90

Led chip flux 3023 [lm]

Luminous flux 2418 [lm]

System power 23 [W]

Luminaire Efficiency 105 [lm/W]

Beam angle 36°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 1,2 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 29.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska