

# DOWNLIGHT QUNA A MINI 930 20W 60° GREY PREMIUM WHITE ON/OFF

Article number: N211-K0001-HE930-HA-R60-ZC01\_500-S8-###



LED	COB
Light colour	3000 [K] PREMIUM WHITE
CRI	90
Led chip flux	2880 [lm]
Luminous flux	2304 [lm]
System power	20 [W]
Luminaire Efficiency	115 [lm/W]
Beam angle	60°
Controller	ON/OFF
MacAdam	3 SDCM

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

### LUMINAIRE

Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 17.09.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska