

DOWNLIGHT QUNA A MINI 935 25W 15° GREY PREMIUM WHITE ON/OFF

Article number: N211-K0001-HE935-HA-R15-ZC02_650-S8-###





LED	СОВ
Light colour	3500 [K] PREMIUM WHITE
CRI	90
Led chip flux	3777 [lm]
System power	3021 [lm]
Luminaire Efficiency	25 [W] 121 [lm/W]
Beam angle	15°
Controller MacAdam	ON/OFF
indo idam	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

LUMINAIRE

Weight	1,2 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

