

DOWNLIGHT

DOWNLIGHT QUNA A MINI 930 19W 15° GREY CRI97 ON/OFF

Article number: N211-K0001-HI930-H8-R15-ZC01_500-S8-###





Lur	a d chip flux minous flux	90 2199 [lm] 1759 [lm]	
Lur		× - 2	
	minous flux	1759 [lm]	
Sys			
	stem power	19 [W]	
Lur	minaire Efficiency	93 [lm/W]	
Bea	am angle	15°	
Со	ntroller	ON/OFF	
Ma	cAdam	3 SDCM	

1,2 [kg]

GREY

Glass

IP 20, IK 3,

220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Weight

Luminaire colour

Operating voltage

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

+48 32 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024