

DOWNLIGHT

DOWNLIGHT QUNA A MINI 930 10W 24° GREY CRI97 ON/OFF

Article number: N211-K0001-HI930-H8-R24-ZC01_250-S8-###





LED	COB
Light colour	3000 [K] CRI97
CRI	90
Led chip flux	1144 [lm]
Luminous flux	915 [lm]
System power	10 [W]
Luminaire Efficiency	92 [lm/W]
Beam angle	24°
Controller	ON/OFF
MacAdam	3 SDCM
LUMINAIRE	
Weight	1,2 [kg]

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage



+48 32 388 80 00

www.cora.pl cora@cora.pl

IP 20, IK 3,

220-240V 50-60Hz

GREY

Glass



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024