


DOWNLIGHT QUNA A MINI 930 23W 36° GREY CRI97 ON/OFF

Article number: N211-K0001-HI930-H8-R36-ZC02_600-S8-###



90 [lm/W]





COB

3000 [K] CRI97 Light colour

CRI

Led chip flux 2601 [lm] Luminous flux 2080 [lm] System power 23 [W]

Beam angle 36° Controller ON/OFF 3 SDCM

MacAdam

LUMINAIRE

Luminaire Efficiency

Weight 1,2 [kg] Protection rating IP , IK , class IP 20, IK 3, GREY Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Housing enables adjustment in two axis planes. Reflector beams available: 15°, 24°, 36° and 60°. Maximum power is 30W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska